



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.25
Insertion Loss	0.05* $\sqrt{f_{GHz}}$
Operating Temperature	- 55~+165°C

Material & Coat-Plating

Inner Conductor	Beryllium bronze gilding
Dielectric	PEI
Body&Nut	Stainless steel SUS303 passivted

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	LUFTEK			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model			
		PRODUCT SPEC	LT-NMD2.4FNMD2.4M NMD2.4 Female NMD2.4 Male			
		APPLICATION SPEC	Connector			
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	
		CUSTOMER DRAWING		SCALE 4: 1	SCALE 4: 1	SHEET 1 OF 1
						RVE 1