



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.25
Insertion Loss	≤0.06* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃

Material & Coat-Plating

Inner Conductor	Beryllium bronze passivation
Dielectric	PEI
Body/Nut	Passivation of stainless steel

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	L\UFT\EK			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model			
		PRODUCT SPEC	LT-NMD2.4M-2.4M NMD2.4 Male 2.4 Male Connector			
		APPLICATION SPEC	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
MATERIAL SEE TABLE		FINISH SEE TABLE	WEIGHT			
		CUSTOMER DRAWING	SCALE 4: 1	SCALE 4: 1	SHEET1 OF 1	RVE 1