

LT-BT-1643G-50 is a bias tee that operates from 16 KHz to 43 GHz. The bias tee offers 4 dB insertion loss and -12 dB typical return loss. The bias tee can handle up to +50 VDC bias voltage and 1.1 A current. The all ports are equipped with 2.92mm female connectors.

Features:

- Ultra Wide Band:16KHz-43GHz
- Low Insertion Loss
- High Voltage
- High Current Capacity

Applications:

- Test Lab
- Sub-assemblies
- System Integrations

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	16KHz-43GHz			
Insertion Loss			4	dB
Ruturn Loss		-12		dB
Isolation		30		dB
DC Voltage			50	V DC
DC Current			1.1	A
RF Power			1	W

Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	2.92mm Female/2.92mm Female	
DC Connector	SMA Female	
Case Material	Aluminum	
Finish	Bue Paint	
Size	30.48*16*12.7	mm

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+50 V
RF Input Power	+30 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm




Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-45		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			



- Notes:
- 1. All data taken @ +23° C unless otherwise specified.
 - 2. Dimensions and specifications may be changed without prior notice.

Typical Performance Data:





Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:





Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.


Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:

Group Delay vs Frequency



Group Delay vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.